

# Zip-Chem® Cor-Ban™

CORROSION INHIBITING COMPOUNDS



- HOME
- AVIATION PRODUCTS
- UNIQUE TECHNOLOGY
- EXACTING CHEMISTRY
- SUPERIOR PACKAGING
- SPECIFICATION GUIDE
- SITE MAP
- NEWS AND PRESS INFO
- CONTACT US

## D-5029NS Corrosion Inhibiting Compound

**DESCRIPTION** Zip-Chem D-5029NS is designed to be a long lasting, high solids, low volatiles, high penetration, water displacing, corrosion inhibiting compound for use on high profile aircraft substrates. The finished coating is non-tacky with a light amber tint.

**APPLICATION** The coating should be applied at 2-3 mils wet thickness. Bulk application is available as ZC-029.

- FEATURES**
- Water Displacing
  - High Penetration
  - Low VOC
  - Detectable Film
  - Solvent Removable
  - Non-Sagging Thixotropic Film
  - Fast Drying Non-Tacky Film
  - > 1500 hours salt spray
  - Non-Cracking and Flaking to -40°F
  - High Solids > 51%



1-800-648-2661

**SPECIFICATIONS** D-5029NS meets or exceeds the following specifications:

- BMS 3-23F TyII
- BMS 3-26
- BMS 3-29
- DMS 2150 Ty 1 & Ty 2

**PHYSICAL PROPERTIES**

**Flash Point:**122°F  
**Specific Gravity:**0.89  
**Viscosity:**140 cps.  
**Water Displacement:**0% Rust  
**Non-Volatiles:**>51% min.  
**Drying Time:**<12 hour  
**Color:**Transparent Amber  
**Exfoliation:**Pass  
**Solvent Type:**Aliphatic  
**Low Temp Flaking:**Pass  
**Penetration:**BMS 3-23F pass  
**Compatibility Cd, Mg, AI:** Pass

**PACKAGING** Aerosol, quarts, gallons, 5 gallons, drums  
Special packaging upon request